



Data sheet KTVE33.7-50



CWL: Continuous running water level



Specification

Electric submersible pump KTVE-series
 Degree of protection IP 68
 Pressure resistance max. 25 m
 Type of impeller semi-vortex
 Max. solid handling 8,5 mm
 Suitable for:
 rain water, ground water, sand water

Electric motor

Dry-type submersible induction motor
 Insulation class E 2Poles 2875 1/min
 Starting mode Direct starting
 Rated voltage 400 V 50 Hz 3~
 Power uptake 4,75 kW
 Rated power 3,70 kW
 Rated current 7,4 A
 Start current 48,0 A

Cable

20m NSSHÖU 4Cx1,5mm²

Motor Protection

Circle thermal protector
 (snap-action bi-metal device)

Shaft seal

Double inside mechanical seal in oil bath
 additional lubrication by oil lifting device
 Primary seal
 Silicon carbide on silicon carbide
 Secondary seal
 Silicon carbide on silicon carbide

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller	FCD700 (EN-GJS-700-2)
Pump casing	Butadiene-/nitrile-rubber
Motor Frame	Aluminium alloy casting
Shaft	SUS403 (EN-X6Cr13)

Discharge size

3" (80mm) Hose Coupling / BS-coupling (optional)

Weight

40 kg (dry weight of the pump only without cable)

Performance curve



KTVE33.7-50

Discharge port	3"
Head	26,5 m
Flow	49,9 m³/h
Rated power	3,70 kW
Power input	4,75 kW
Phases	3~
Voltages	400 V
Frequency	50 Hz
Rated current	7,4 A
Starting current	48,03 A
Number of poles	2
Speed	2875 1/min
Starting mode	Direct starting
Insulation class	E



Dimensions


KTVE33.7-50



KTVE33.7-50

CWL: Continuous running water level
LWL: Lowest running water level

Sectional drawing KTVE33.7-50



KTVE33.7-50

No.	Description	Remark	No.	Description	Remark
1	Cable	20m NSSHÖU	55	Rotor	.
20	Pump casing	Butadiene-/nitrile-rubber	56	Stator	.
21	Impeller	FCD700 (EN-GJS-700-2)	58	Locking washer	SUS304 (EN-X5CrNi18-10)
23	Strainer	Steel plate	64	Motor Frame	Aluminium alloy casting
25	Mechanical seal	H-25	68	Handle	Steelplate + butadieneacrylnitrilerubber
29	Oil casing	Aluminium alloy casting	71	Shaft protection sleeve	SUS304 (EN-X5CrNi18-10)
31	Attrition plate	Butadiene-/nitrile-rubber	90	Electrode	.
32	Discharge coupling	Aluminium alloy casting	121	Wear protection	Styrene-butadiene-rubber
35	Oil screw	SUS304 (EN-X5CrNi18-10)	122	V-ring	Butadieneacrylnitrilerubber
36	Lubricant	Turbine oil (ISO VG32)	127	Pressure plate	Steel plate
50	Motor cover	Aluminium alloy casting			
51	Main cover	Aluminium alloy casting			
52A	Upper bearing	6204ZZC3			
52B	Lower bearing	6306ZZC3			
53	Motor Protection	.			
54	Shaft	SUS403 (EN-X6Cr13)			