



Data sheet 37-BER5



1 ... Air quantity - Water depth

2 ... Output kW - Water depth

Specification

Electric submersible aerator BER
 Degree of protection IP 68
 Pressure resistance max. 5m
 Type of impeller
 Free passage 35 mm
 Suitable for:
 aeration of activated sludge
 (municipal sewage only)

Electric motor

Dry-type submersible induction motor
 Insulation class E, 4 Pole, 1410 U/min
 Starting mode Direct on line start
 Rated voltage 400V, 50Hz, 3-phase
 Rated power 3.7 kW
 Power uptake 4.59 kW
 Rated current 7.9 A
 Start current 49 A

Cable

10m H07RN-F 4Cx1,5mm²

Motor Protection

Circle thermal protector
 (snap-action bi-metal device)

Shaft seal

Double inside mechanical seal in oil bath
 additional lubrication by oil lifting device
 Primary seal
 Silicon carbide on silicon carbide
 Secondary seal
 Ceramic on carbon

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller FC200 (EN-GJL-200)
 Pump casing FC200 (EN-GJL-200)
 Suction cover FC200 (EN-GJL-200)
 Motor Frame FC200 (EN-GJL-200)
 Shaft DIN 1.4028 (EN-X30Cr13)
 Ejector free standing type DIN 1.0040 nylonbonded
 TOS-Ejector guide rail fitting type DIN 1.0040 nylonbonded

Weight

91 kg (dry weight of the pump only without cable)


Air passage

2" (50mm) screwed-in mating flange

Performance curve

37-BER5



Air passage	2"
Air quantity	80 Nm³/h
water depth	3 mAq
max. water depth	5 mAq
Rated power	3.70 kW
Power input	4.59 kW
Phases	3
Voltages	400 V
Frequency	50 Hz
Rated current	7.9 A
Starting current	49.0 A
Number of poles	4
Speed	1410 U/min
Starting mode	Direct on line start
Insulation class	E



37-BER5

Dimensions

37-BER5



37-BER5

CWL: Continuous running water level
LWL: Lowest running water level


TSURUMI PUMP

Tsurumi (Europe) GmbH
2025-03-03 V.01.02.2025

Wahlerstr. 10 • 40472 Düsseldorf • Germany
Tel.: +49-211-4179373 sales@tsurumi.eu
Fax: +49-211-417937-480 www.tsurumi.eu

Sectional drawing

37-BER5



37-BER5

No.	Description	Remark	No.	Description	Remark
1	Cable	NSSHÖU	55	Rotor	.
20	Pump casing	FC200 (EN-GJL-200)	56	Stator	.
21	Impeller	FC200 (EN-GJL-200)	60	Bearing Housing	FC200 (EN-GJL-200)
22	Suction cover	FC200 (EN-GJL-200)	64	Motor Frame	FC200 (EN-GJL-200)
23	Stand	Steel plate SPCC	72	Eye screw (2x)	DIN 1.4301 (EN-X5CrNi 18-10)
25	Mechanical seal	H-35A	95	Lifting chain	Construction steel SS400
26	Oil seal	TC507212	151	Air passage	FC200 (EN-GJL-200)
30	Oil distributor	Plastic	153	Diffuser	DIN 1.0040 nylonbonded
35	Oil screw (2x)	DIN 1.4301 (EN-X5CrNi 18-10)			
36	Lubricant	Turbine oil (ISO VG32)			
46	Air vent valve	Nylon			
49	Bottom Plate	Steel plate SPCC			
52A	Upper bearing	630ZZC3			
52B	Lower bearing	6309ZZC3			
53	Motor Protector 380/400/415V-50Hz	KA314-HRXL00 (H.C)			
54	Shaft	DIN 1.4028 (EN-X30Cr13)			